



MATERIAL SAFETY DATA SHEET

SECTION I - MANUFACTURER IDENTIFICATION

CASCADE ASPHALT SEALING CO
6238 SOUTH TACOMA WAY
TACOMA, WA 98409

EMERGENCY PHONE: CHEMTREC 1-800-424-9300
INFORMATION PHONE: 1800-846-9125
DATE PREPARED: MAY 7, 2009

SECTION II - PRODUCT IDENTIFICATION

PRODUCT NAME: POURABLE CRACK FILLER
PRODUCT CODE: A-400

SECTION III - HAZARDOUS INGREDIENTS / SARA III INFORMATION

HAZARDOUS COMPONENTS	CAS #	OSHA PEL mg/M3	ACGIH TLV mg/M3	OTHER	% (OPT)
Asphalt Residual	08052-42-4	5.0	5.0 (fume)		<60.00
Synthetic Polymer	108-05-4				<10.00
Crystalline Silica Quartz	7631-86-9	0.1	0.1		< 5.00
Water	7732-18-5				<35.00
Aluminum Silicate	1332-58-7	0.1	0.1		<10.00
Health: 1	Flammability: 0	Reactivity: 0	Ratings based on NFPA		

SECTION IV - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT: 212°F
SPECIFIC GRAVITY (H₂O=1): 1.10
VAPOR PRESSURE (mm Hg): NA
MELTING POINT: NA
VAPOR DENSITY (AIR=1): Heavier
EVAPORATION RATE (Butyl Acetate=1): Water
SOLUBILITY in WATER: Soluble
APPEARANCE and ODOR: Black, Pungent Odor

SECTION V - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method Used): NA
FLAMMABLE LIMITS: LEL: NA UEL: NA
EXTINGUISHING METHOD: Water, all purpose (ABC) dry chemical, CO₂ foam.
SPECIAL FIRE FIGHTING PROCEDURES: Although this material will not burn, if it is in the fire area, an approved, self-contained breathing apparatus should be worn to prevent exposure to thermal decomposition products and residual monomers.
UNUSUAL FIRE AND EXPLOSION HAZARDS: **NON FLAMMABLE in EMULSION STATE.**
NOTE: In Asphalt State: Small fires-use dry chemical, CO₂, Halon Water spray or standard foam. Large fires-use water spray, fog or standard foam.

SECTION VI - REACTIVITY DATA

CONDITIONS TO AVOID: Avoid heat, sparks or open flame.

INCOMPATIBILITY (MATERIAL TO AVOID): Any strong oxidizing agents.

HAZARDOUS POLYMERIZATION: Will not occur.

STABILITY: Stable.

SECTION VII - HEALTH HAZARD DATA

CARCINOGENITY: NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No

SIGNS and SYMPTOMS of EXPOSURE:

EYES: May cause mild irritation.

SKIN: May cause slight to mild irritation.

INHALATION: May cause dizziness, headache, nausea.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Individuals with chronic respiratory disorders may be adversely affected by any fume or airborne particle matter exposure.

EMERGENCY and FIRST AID PROCEDURES:

INHALATION: Remove from contaminated area. If breathing is difficult, give oxygen. If breathing stops, give artificial respiration - Call Physician.

INGESTION: If conscious give 1 to 2 glasses of milk or water, induce vomiting and call a physician. ***NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.***

EYES: Immediately flush with water for at least 15 minutes holding eyelids open. Call a physician if irritation develops.

SKIN: Remove contaminated clothing and launder before reuse. Wash skin with soap and water.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all ignition sources. Avoid breathing vapors. Open all windows and doors. Keep out of sewers and water sources. Advise proper authorities.

WASTE DISPOSAL METHODS: As provided under Resources Conservation and Recovery Act (RCRA), and in accordance with Federal, State and Local Regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep containers closed when not in use. Do not handle or store near heat, sparks or open flame or strong oxidants.

OTHER PRECAUTIONS: Avoid breathing vapors. Avoid prolonged or repeated skin contact.

SECTION IX - CONTROL MEASURES

RESPIRATORY PROTECTION: Use a NIOSH approved respirator.

VENTILATION: Must be adequate, use local exhaust as needed.

PROTECTIVE GLOVES: Use rubber gloves as needed.

EYE PROTECTION: Use goggles or face shield.

OTHER PROTECTIVE CLOTHING or EQUIPMENT: As needed to avoid skin contact.

WORK / HYGIENIC PRACTICES: Wash skin and exposed clothing thoroughly with soap and water after use.