# Dura-Fill

# **Material Safety Data Sheet**

Page 1

#### Section One: Product Identification

Product Name: Dura-Fill brand hot melt crack and joint sealants.	Note: This MSDS complies with requirements of the Hazardous Communication Standard, OSHA 29 CFR 1910.1200	
Chemical Name, Family & Synonyms: Rubber Modified Asphalt Materials	Hazard Classification: Health = 1	
Formula: Mixture contains asphalt cement, rubbers, extenders, and reinforcing fillers	Fire = 1	
	Reactivity = 0	
DOT Shipping Classification: Non Haz Mat	Emergency Assistance: 419-621-1966	

Section Two: Hazardous Ingredients / Identity Information

Hazardous Components (Specific Chemical Identity / Common Name)	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (opt)
Asphalt (CAS 8052-42-4)		5 mg / m <sup>3</sup>		

**Section Three: Physical Chemical Characteristics** 

Boiling Point: Greater than 600oF	Specific Gravity: (H <sub>2</sub> O = 1) 1.0-1.3
Vapor Pressure: (mm Hg) Not Applicable	Melting Point: (ASTM-D36, Ring and Ball Softening Point) 160-220°F
Vapor Density: (AIR=1) Not Applicable	Evaporation Rate: (Butyl Acetate=1) NA
	Material does not experience evaporation
Solubility in Water: Negligible	Appearance and Odor: Black adhesive, odor of petroleum,
	Solid at 77oF/ liquid above 275°F

Section Four: Fire and Explosive

Flash Point: (Method Used) C.O.C. (ASTM-D92)	Special Fire Procedures: Use of self controlled breathing apparatus in
424°F Minimum	enclosed areas and full body protection gear including face shield, trench
Flammable Limits: NA	coats, gloves, and rubber boots. Concentrated vapors from combustion
	should not be breathed.
LEL	Unusual Fire and Explosion Hazards: Material will not burn unless pre-
UEL	heated. Black, dense, hazy smoke forms during burning. Keep sparks
Extinguishing Media: CO <sub>2</sub> , Dry Chemical, Foam	away from concentrated fumes.



CASCADE ASPHALT SEALING CO 6238 SOUTH TACOMA WAY TACOMA, WA 98409 **EMERGENCY PHONE: CHEMTREC 1-800-424-9300** 

**INFORMATION PHONE: 1800-846-9125** 

**DATE PREPARED: MAY 7, 2009** 



## **Material Safety Data Sheet**

Page 2

#### **Section Five: Reactivity Data**

Stability: Stable	Conditions to Avoid: Do NOT expose fumes from heated product to sources of ignition.
Incompatibility: Strong oxidizing materials	Hazardous Decomposition or Byproducts: Combustion may produce various oxides of carbon. (CO, CO <sub>2</sub> )
Hazardous Polymerization: Will NOT Occur	Conditions to Avoid: None Known

#### Section Six: Health and Hazard Data

Routes of Entry:	Inhalation: Yes, fumes Skin: Yes, hot material Ingestion: Rare	Health Hazards (Acute/Chronic): High fume concentrations may irritate eyes and respiratory tract. Hot product may cause minor to severe burns when contacts skin.
Carcinogenity:	NTP: NO IARC Monographs: No OSHA Regulated: No	Signs and Symptoms of Exposure: Inhalation-irritation, nausea, dizziness, headaches Skin Contact with Solid Product - No Irritation Skin Contact with Hot Product - Burns
Medical Conditions: Respiratory problems may be aggravated by petroleum fumes		Emergency and First Aid Procedures: Inhalation: Remove to fresh air, assist breathing if necessary Burns: Cool with water, remove with mineral oil/soap/water Get medical help for severe burns

#### Section Seven: Precautions for Safe Handling and Use:

Steps to be taken in case material is released or spilled: Permit material to cool to a solid, Cover with earth to reduce adhesiveness, Place in appropriate containers to transport to a waste disposal site

Waste Disposal Method: Burry collected material in approved landfill or burn in approved incinerator; Follow local, state, & federal regulations

Precautions taken in Handling & Storing: Keep pallets intact in storage, Packages of unused material present no known health / safety hazards

**Other Precautions**: Be aware of burn hazards, which are possible if skin contact occurs during use. Avoid inhalation of excessive amounts of fumes, Practice good personal hygiene.

### **Section Eight: Control Measures**

Respiratory Protection: In high fume concentration, NIOSH respirator with organic and mist filter

Ventilation: Local Exhaust to keep fumes below TLV, Mechanical and Specialty Ventilation not generally required

Protective Gloves: To protect hands and arms from hot material

Eye Protection: Safety Goggles

Other Protective Clothing/Equipment: To prevent skin contact with hot material

Work/Hygienic Practices: Use good personal hygiene, wash hands and exposed skin with soap and water