

MATERIAL SAFETY DATA SHEET

SECTION I - MANUFACTURER IDENTIFICATION

CASCADE ASPHALT SEALING CO.
6238 SOUTH TACOMA WAY
TACOMA, WA 98409

EMERGENCY TELEPHONE NO CHEMTREC: 1-800-424-9300
INFORMATION NUMBER 1-800-846-9125
DATE PREPARED MAY 1, 1009

SECTION II - PRODUCT IDENTIFICATION

PRODUCT NAME: Fast Dry
PRODUCT CODE: A-625

SECTION III - HAZARDOUS INGREDIENTS / SARA III INFORMATION

HAZARDOUS COMPONENTS	CAS #	OSHA PEL mg/M3	ACGIH TLV mg/M3	OTHER	% (OPT)
Asphalt Residual	08052-42-4	5.0	5.0 (fume)		<20.00
Water	7732-18-5				<30.00
Acrylic Polymer	NA Mixture				<60.00
Crystalline Silica	14808-60-7	0.1	0.1		<10.00
Calcium Carbonate	1317-65-3	10.0	10.0		<25.00
Magnesium Silicates	14807-96-6				<15.00
Carbon Black Pigment	1333-84-4				< 5.00

Health: 1 **Flammability:** 0 **Reactivity:** 0 Ratings based on NFPA

SECTION IV - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT: 212°F
SPECIFIC GRAVITY (H2O=1): 1.50
VAPOR PRESSURE (mm Hg): NA
MELTING POINT: NA
VAPOR DENSITY (AIR=1): Heavier
EVAPORATION RATE (Butyl Acetate=1): Water
SOLUBILITY in WATER: Soluble
APPEARANCE and ODOR: Black, No Odor

SECTION V - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method Used): NA
FLAMMABLE LIMITS: LEL: NA UEL: NA
EXTINGUISHING METHOD: Water, all purpose (ABC) dry chemical, CO2 foam.
SPECIAL FIRE FIGHTING PROCEDURES: Although this material will not burn, if it is in the fire area, an approved, self-contained breathing apparatus should be worn to prevent exposure to thermal decomposition products and residual monomers.
UNUSUAL FIRE AND EXPLOSION HAZARDS: **NON FLAMMABLE in EMULSION STATE.**
NOTE: In Asphalt State: Small fires-use dry chemical, CO2, Halon Water spray or standard foam. Large fires-use water spray, fog or standard foam.